



DECOTRON[®] M50

Water-based cleaning agent designed for manual cleaning of low-contaminated soldering machines and parts.

Ready-mix designed for direct use. Designed for cleaning of most types of flux. Developed for areas with common contamination levels, minimum smell.

Recommended areas for use

Removal of flux residues, dust and grease from reflow ovens, soldering waves and other contaminated surfaces

Instructions for use

Turn the manual sprayer nozzle from position STOP by 90 ° before first use. Then apply a necessary amount on the surface to be cleaned, wait for several minutes and wipe the surface using a smooth piece of cloth. Repeat the procedure if necessary.



Information

- High compatibility with material and components of the cleaned devices
- Leave no residue or odor
- Specially developed for cleaning of elements of reflow ovens
- No flash point
- Suitable for cleaning of flux residues of all types of soldering flux
- Environmentally-friendly – biodegradable
- A special sprayer creates “active foam” which remains active on vertical surfaces for a longer time

Table of physical and chemical properties

Product appearance:	clear liquid
Colour:	transparent
Odour:	ether-like
pH value:	10 - 11
VOC content:	8 %
Flash point:	non-flammable
Density at 25 °C:	0,99 kg/l



Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Date of revision:
07. 06. 2021

Check SDS prior to use.
Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron[®] is a registration trademark
of DCT Czech s.r.o.



DECOTRON® M50

General information



Packing

1 litre bottle; 5, 10, 25 litre can



Transport

UN number: 1824

Transport hazard class: 8



Handling

Wear nitrile gloves while manipulating with cleaning agent.

It is necessary to stir well the can before use.



Storage

Should be stored in closed containers, in ventilated areas

At temperature 5 – 25 °C



Shelf life:

The minimum shelf life for this product is 5 years.

Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.



We are certified as part of a worldwide quality management system by LLOYD'S.

Date of issue:
07. 06. 2021

Check SDS prior to use.
Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron® is a registration trademark of DCT Czech s.r.o.