



# Antifoam 03

Water dispersible chemical defoaming agent.

## Recommended areas for use

To knock down the foam in cleaning or rinsing fluid in spray in air or air bubble cleaning systems.



## Instructions for use

Dilution ratio: **1:100**

Recommended process temperature: 25 – 45°C

Shake before use



## Product information

- Possess lower surface tension than the system to which is added
- Disperse readily in the system
- Leave no residue or odor
- Doesn't contain silicone

## Physical and chemical properties

Product appearance:	milky liquid
Odour, aroma:	organic
VOC content:	60%
pH:	7
Flash point:	no
Density at 20°C:	0,98 kg/l



Date of issue/revision:  
**27 March 2017**

Consult **MSDS** prior to use.



# Antifoam 03

## General information



### Packing

1 litres, 5 litres



### Transport

UN number: No.

Transport hazard class: No.



### Handling

Wear nitrile gloves while manipulation with the cleaning fluid.



### Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25 °C.



### Shelf life

The minimum shelf life for this product is 2 years.

Return the used product for proper disposal to the nearest authorized collection location.

## Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at [www.dct.cleaning](http://www.dct.cleaning)

## Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds



RoHS  
Compliant



REACH  
SVHC



BIODEGRADABLE

We are certified as part of a worldwide quality management system by **LLOYD'S**



Date of issue/revision:  
27 March 2017

Consult **MSDS** prior to use.