



DECOTRON® T332

Water-based cleaning fluid determined for maintenance cleaning of flux residues from soldering frames, soldering furnaces filters and waves after soldering process.

Specially developed for cleaning filter elements of REHM furnaces.

Ready-mix, intended for direct use.

Effective for all types of solder pastes and most types of SMT adhesives

Intended for use in all types of cleaning machines, mainly in the high pressure spray-in-air cleaning machines.



Recommended areas for use

- 1. flux from filter elements of soldering furnaces**
- 2. flux from filter elements of soldering waves**
- 3. flux from soldering frames**

Recommended cleaning technology

Air bubble, High pressure spray-in-air
 Air bubble, High pressure spray-in-air
 Air bubble, High pressure spray-in-air

Recommended cleaning process

Cleaning technology	Cleaning	1. rinse	2. rinse	Drying
Air bubble	Decotron® T332	X	water	Hot air
High pressure spray-in-air	Decotron® T332	X	water	Hot air



Product information

- the fluid is alkaline, rinse with water needed
- high compatibility with material and components of the cleaning devices
- specially developed for cleaning of elements of REHM furnaces - high efficiency of cleaning / high compatibility with filter elements material filtračních elementů
- environment-friendly - biodegradable
- tenside-free, no solid residues on the surface being cleaned
- no flash point, can be heated to increase the cleaning efficiency



Table of physical and chemical properties

Product appearance:	colourless/yellowish clear liquid
Odour, aroma:	ether-like
pH value:	10.9
VOC content:	13%
Recommended process temperature:	35 – 55 °C
Flammability point:	non-flammable
Flash point:	non-flammable
Density at 25 °C:	0,99 kg/l



Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Date of issue/revision

Consult MSDS prior to use.

Decotron® is a registration trademark of DCT Czech s.r.o.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress

01 October, 2019



DECOTRON® T332

General information



Packing

25 litres, 5 litres can



Transport

Product is not hazardous for transport.



Handling

Wear nitrile gloves while manipulation with the cleaning fluid.

It is necessary to stir well the can before use.



Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25°C.



Shelf life

The minimum shelf life for this product is 5 years.

Return the used product for proper disposal to the nearest authorized collection location.

Technical support

For process implementation and setting, optimization and solving of process issues, trial test, Contact your DCT specialist at www.dct.cleaning.

Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds



RoHS
Compliant



REACH
SVHC



BIODEGRADABLE

We are certified as part of a worldwide quality management system by LLOYD'S



Date of issue/revision

01 October, 2019

Consult MSDS prior to use.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress

Decotron® is a registration trademark of DCT Czech s.r.o.