



# DECOTRON® 239

Water-based cleaning fluid determined to remove residues of a solder paste and uncured epoxy based SMT adhesives from printing stencils, PCBs misprints and squeegee. Effective cleaning of process residues (dust, grease) from aluminium parts and plastics with good evaporation properties after cleaning.

### Recommended areas for use

Recommended cleaning technology

Solder paste, uncured epoxy based SMT adhesive, grease, dust particles, imprints

Spray-in-air

### Process table

Cleaning technology	Cleaning	1. rinse	2. rinse	Drying
Spray-in-air	DECOTRON® 239, 45°C	X	DECOTRON® 239/DI water	Hot air

### Product information

- neutral, one phase water based cleaning fluid
- designed for special applications into clean room environment
- fast evaporation rate, doesn't leave oily film on the surface after drying
- recommended for use as rinsing fluid where fast drying is needed due to high evaporation rate
- no flash point, can be heated to increase the cleaning efficiency
- ready-mix, intended for direct use effective cleaning in 15 % solution
- excellent compatibility with broad materials, plastics, aluminium, inks and labels

### Table of physical and chemical properties

Product appearance:	clear fluid
Odour, aroma:	organic
pH value (15% in water):	7
VOC content:	15%
Recommended process temperature:	45°C
Flash point:	non-flammable
Density at 20°C:	0,98 kg/l
Number of stages:	1



### Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at [www.dct.cleaning](http://www.dct.cleaning)



Date of issue:  
30 August, 2016

Detailed information can be found in the Safety Data Sheet of **DECOTRON® 239**.

**DECOTRON®** is a registration trademark of DCT Czech s.r.o.



# DECOTRON® 239



## Packing

25 litres can



## Transport

Product is not hazardous for transport.



## Handling

It is necessary to stir well the can before use.



## Storage

Should be stored in closed containers, in ventilated areas at the temperature from 5 to 25°C.



## Best before

The maximum usable life for this product is 60 months from the production date.



**RoHS**  
Compliant



**REACH**  
SVHC



**BIODEGRADABLE**



Date of issue:  
**30 August, 2016**

Detailed information can be found in the  
Safety Data Sheet of **DECOTRON® 239**.

**DECOTRON®** is a registration trademark  
of DCT Czech s.r.o.

ver. 1.2